



TW-Kupplung Typ MK mit BSPP – Innengewinde (nur Kronenring) mit CSM Lippendichtung und PTFE Gewindedichtung

Female coupler type MK BSPP female thread (only crown) – CSM lip gasket PTFE thread-gasket
Raccord type MK taraudé femelle BSPP (uniquement la couronne) – Joint CSM pour raccord - Joint de filetage PTFE
TW-Acople hembra tipo MK con rosca hembra BSPP (solo corona) - Junta labial CSM Junta de rosca de PTFE
TW Gniazdo typ MK z gwintem wewnętrznym BSPP (Korona) – Uszczelka profilowa CSM Uszczelka o-ring PTFE
TW-Tipo MK con filettato femmina BSPP (corona) – CSM guarnizione filettato PTFE

Part-No.	Material	WP	Dimension	Thread	Price
2MKSK	SS 1.4408	16 bar	DN50	G2"	
3MKSK	SS 1.4408	16 bar	DN80	G3"	



TW - Kupplung Typ VK mit BSPP - Innengewinde mit PTFE Gewindedichtung

Male adapter type VK BSPP female thread - PTFE thread-gasket
Raccord type VK taraudé femelle BSPP - Joint de filetage PTFE
TW- Racor macho tipo VK con rosca hembra BSPP- Junta de rosca PTFE
TW Wtyk typ VK z gwintem wewnętrznym BSPP- Uszczelka o-ring PTFE
Raccordo maschio tipo VK filettato femmina BSPP - Guarnizione filettato PTFE

Part-No.	Material	WP	Dimension	Thread	Price
2VKS	SS 1.4408	16 bar	DN50	G2"	
3VKS	SS 1.4408	16 bar	DN80	G3"	
4VKS	SS 1.4408	16 bar	DN100	G4"	

