

Schwere Baureihe

Metrisches Feingewinde, zylindrisch

Abdichtung: Außengewindenippel mit 24° Aussenkantung

Heavy duty

Metric fine thread, cylindric

Sealing: outer thread hose nipple with 24° chamfer

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	RA PJ	H (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
420	-03	5	3/16"	M 14X1,5	S06	23	48	14	424 17 05 14
420	-03	5	3/16"	M 16X1,5	S08	23	48	17	424 17 05 16
450	-04	6	1/4"	M 14X1,5	S06	23	51	14	424 17 06 14
450	-04	6	1/4"	M 16X1,5	S08	23	51	17	424 17 06 16
450	-04	6	1/4"	M 18X1,5	S10	24	52	19	424 17 06 18
450	-04	6	1/4"	M 20X1,5	S12	25	53	22	424 17 06 20
450	-05	8	5/16"	M 18X1,5	S10	24	52	19	424 17 08 18
440	-05	8	5/16"	M 20X1,5	S12	25	53	22	424 17 08 20
450	-06	10	3/8"	M 18X1,5	S10	24	55	19	424 17 10 18
450	-06	10	3/8"	M 20X1,5	S12	25	56	22	424 17 10 20
450	-06	10	3/8"	M 22X1,5	S14	27	58	24	424 17 10 22
450	-06	10	3/8"	M 24X1,5	S16	30	60	27	424 17 10 24
450	-08	12	1/2"	M 20X1,5	S12	12	60	22	424 17 12 20
420	-08	12	1/2"	M 22X1,5	S14	28	61	24	424 17 12 22
420	-08	12	1/2"	M 24X1,5	S16	29	62	24	424 17 12 24
350	-08	12	1/2"	M 30X2	S20	34	67	32	424 17 12 30
420	-10	16	5/8"	M 24X1,5	S16	30,5	66,5	27	424 17 16 24
350	-10	16	5/8"	M 30X2	S20	32	68	32	424 17 16 30
350	-12	19	3/4"	M 30X2	S20	33	74	32	424 17 20 30
350	-12	19	3/4"	M 36X2	S25	37	78	36	424 17 20 36
280	-16	25	1"	M 36X2	S25	39	90	36	424 17 25 36
280	-16	25	1"	M 42X2	S30	43	94	46	424 17 25 42
210	-16	25	1"	M 52X2	S38	50	104	55	424 17 25 52
210	-20	31	1 1/4"	M 42X2	S30	44	101	46	424 17 32 42
210	-20	31	1 1/4"	M 52X2	S38	48	105	55	424 17 32 52
185	-24	38	1 1/2"	M 52X2	S38	48	112	55	424 17 40 52

