



Test Coupling with Male Threaded Stud SKK-12



Ordering Codes

SKK-12*-G1/4*-B*-C*-KK*-W3

* Type	Test Coupling with Piston Valve	SKK
* Series	STAUFF Test 12 (Connection Thread S12,65 x 1,5)	-12
* Port Connection	acc. to dimension table	-G1/4
* Seal Material	NBR (Buna-N®)	-B
	FKM (Viton®)	-V
	EPDM	-E
	Seal Type B and D	none
* Seal Type	O-ring Type A	-A
	Metal Joint Type B	-B
	Elastomeric Sealing Type C	-C
	Taper Type D	-D
	O-ring Type E	-E
* Protection Cap	Knurled protection cap	-
	Plastic protection cap	-KK
* Material Code	Steel, zinc/nickel-plated	-W3
	Stainless Steel V2A - 1.4305 (AISI 303)	-W4
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W5

Seal Type



O-ring Type A



Metal Joint Type B



Elastomeric Sealing Type C


Taper Type D¹


O-ring Type E

Thread	Seal Type	Working Pressure (^{bar} /psi)	Dimensions (^{mm} / ⁱⁿ)			Torque (^{Nm} / ^{ft-lb}) ca.	Weight (^{kg} / ^{lbs}) ca.	Ordering Codes (Standard Option)
T			h1	h2	Hex	Thread T	per 100	
M8 x 1	Type A	250	38	8,5	14	6	5,50	SKK-12-M8x1-B-A-W3
		3625	1.50	.33	.55	4.4	12.10	
		630	35	9,8	14	12	5,30	SKK-12-M10x1-B-A-W3
M10 x 1	Type A	9137	1.38	.39	.67	8.8	11.66	
		630	31	12	17	35	5,60	SKK-12-M12x1.5-B-W3
M12 x 1,5	Type B	9137	1.22	.47	.67	25.8	12.35	
		630	31	12	19	55	6,40	SKK-12-M14x1.5-B-W3
M14 x 1,5	Type B	9137	1.22	.47	.75	40.6	14.08	
		630	31	12	22	70	8,10	SKK-12-M16x1.5-B-W3
M16 x 1,5	Type B	9137	1.22	.47	.87	51.6	17.82	
		630	30	12	19	55	6,10	SKK-12-G1/4-B-W3
G1/4	Type B	9137	1.18	.47	.75	40.6	13.42	
		630	31	12	22	90	7,80	SKK-12-G3/8-B-W3
G3/8	Type B	9137	1.22	.47	.87	66.4	17.16	
		630	31	12	17	35	5,70	SKK-12-M12x1.5-B-C-W3
M12 x 1,5	Type C	9137	1.22	.47	.67	25.8	12.54	
		400	40	8	14	18	5,90	SKK-12-G1/8-B-C-W3
G1/8	Type C	5801	1.57	.31	.55	13.3	12.98	
		630	31	12	19	45	6,30	SKK-12-G1/4-B-C-W3
G1/4	Type C	9137	1.22	.47	.75	33.2	13.86	
		400	33	8	17		5,00	SKK-12-R1/8K-D-W3
R1/8 K	Type D ²	5801	1.30	.31	.55		11.00	
		630	30	12	17		5,40	SKK-12-R1/4K-D-W3
R1/4 K	Type D ²	9137	1.18	.47	.55		11.88	
		400	33	10	14		5,00	SKK-12-1/8NPT-D-W3
1/8 NPT	Type D ²	5801	1.30	.39	.55		11.00	
		630	28	15	14		5,50	SKK-12-1/4NPT-D-W3
1/4 NPT	Type D ²	9137	1.10	.59	.55		12.10	
		400	38	7,5	14	8	5,40	SKK-12-5/16UNF-B-E-W3
5/16-24 UNF	Type E	5801	1.50	.30	.55	5.9	11.88	
		630	33	9,1	17	20	5,90	SKK-12-7/16UNF-B-E-W3
7/16-20 UNF	Type E	9137	1.30	.36	.67	14.7	12.98	
		630	32	9,2	17	25	5,90	SKK-12-1/2UNF-B-E-W3
1/2-20 UNF	Type E	9137	1.26	.36	.67	18.4	12.98	
		630	31	10	19	35	6,30	SKK-12-9/16UNF-B-E-W3
9/16-18 UNF	Type E	9137	1.22	.39	.75	25.8	13.86	
		630	32	11	17	35	5,80	SKK-12-M12x1.5-B-E-W3
M12 x1,5	Type E	9137	1.26	.43	.67	25.8	12.79	

¹ Special thread: buttress thread S12,65 x1,5

² Suitable liquid / plastic sealant required.

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Torque recommendations for Steel mating material.

For further information on Seal Types,
please see page 74-77.