

Water max 130°C 400 bar Hygienic hose

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series. For example: 302/35/SO

FIXED S. STEEL AISI 304



Supplied with:

- hose in synthetic rubber with blue hygienic covering with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- Teflon® seals
- central shaft in stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hygienic hose supplied	Connection	
			Inlet	Outlet
S. 300	302/35	without hose	F 3/8"G	F 3/8"G
	303/36	12m 5/16" (946/12)	F 3/8"G	M 3/8"G
S. 350	352/35	without hose	F 3/8"G	F 3/8"G
	353/31	12m 5/16" (946/12)	F 3/8"G	M 3/8"G
S. 430	434/35	without hose	F 3/8"G	F 1/2"G
	433/38	10m 3/8" (906/10)	F 3/8"G	F 3/8"G
	433/39	15m 3/8" (906/15)	F 3/8"G	F 3/8"G
S. 530	534/35	without hose	F 3/8"G	F 1/2"G
	533/37	25m 3/8" (906/25)	F 3/8"G	F 3/8"G
S. 560	564/35	without hose	F 3/8"G	F 1/2"G
	563/36	40m 3/8" (906/40)	F 3/8"G	F 3/8"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.



Atex 94/9

- II 3GD c X (only for series 300-350-4430 ABS)
- IIB 2GD c T4 T135°C X

USES

