



### UMETA Filling Device for Grease Guns

All grease guns with a DIN filler valve can be filled from the bucket easily and safely by the inclined filling coupler. With variable screw-on features, the filling devices work with all common bucket sizes. The loose lid protects against dirt and grime and serves for simple control of filling height at the same time.

delivery capacity  
operating pressure

30 ccm (1.1 oz.)/stroke  
8 bar / 1.2 PSI

packed in  
weight

cardboard box  
in kgs, incl. packaging



| Content<br>grease bucket | Grease Bucket<br>Ø | Bucket height max.<br>in mm (inches) | Weight<br>in kgs | Dimensions (L x W x H)<br>in mm | Ref. No.: |
|--------------------------|--------------------|--------------------------------------|------------------|---------------------------------|-----------|
| 5 kg                     | 180 – 210 mm       | 510 (20")                            | 3.8              | 670 x 420 x 100                 | 7591783   |
| 10 kg                    | 210 – 240 mm       | 510 (20")                            | 3.9              | 670 x 420 x 100                 | 7591883   |
| 15 kg                    | 240 – 270 mm       | 510 (20")                            | 4.3              | 670 x 420 x 100                 | 7591483   |
| 20 kg                    | 270 – 310 mm       | 510 (20")                            | 4.8              | 670 x 420 x 100                 | 7591983   |
| 25 kg                    | 310 – 335 mm       | 680 (26.8")                          | 5.4              | 670 x 420 x 100                 | 7591583   |
| 50 kg                    | 335 – 385 mm       | 680 (26.8")                          | 6.5              | 800 x 420 x 100                 | 7591683   |



### UMETA Handlever Oil Barrel Pump (steel tube)

- with telescopic tube and steel discharge elbow
- for 60/200/220 ltr. drums
- suitable for motor, hydraulic, and gear oil, diesel, petroleum, heating oil, waste oil

|                   |   |  |                    |
|-------------------|---|--|--------------------|
| suitable for      | motor, hydraulic, and<br>gear oils up to SAE 50     | total height                                   | 1,250 mm (49.2")   |
| tube type         | made of zinc-plated steel                           | total width                                    | 520 mm (20.5")     |
| length/dip depth  | 440 – 860 mm (17.3" - 33.9")                        | net weight                                     | 1,800 g (63.5 oz.) |
| tube Ø            | 25 – 35 mm (1.0" x 1.4")                            | packed in<br>cardboard box                     |                    |
| drum thread       | 2"  | gross weight                                   | 1,900 g (67 oz.)   |
| delivery capacity | 16 ltr. (541 oz.)/min.<br>300 ccm (10.1 oz.)/stroke | dimensions (L x W x H)<br>(18.1 x 5.5 x 2.75") | 460 x 140 x 70 mm  |

Packaging  
cardboard box

Ref. No.:  
9626830



### UMETA Rotary Oil Barrel Pump

- with steel tube and steel discharge elbow
- for 60/200/220 ltr. drums
- comes with: 1 m PVC hose with fold protection spring, 2 hose clamps

|                   |                           |                            |                     |
|-------------------|---------------------------|----------------------------|---------------------|
| tube type         | made of zinc-plated steel | total width                | 210 mm (8.3")       |
| length/dip depth  | 980 mm (38.6")            | net weight                 | 4,800 g (169 oz.)   |
| tube Ø            | 25 – 35 mm (1.0" x 1.4")  | packed in<br>cardboard box |                     |
| drum thread       | 2"                        | weight                     | 4,900 g (173 oz.)   |
| delivery capacity | 35 ltr. (1,183 oz.)/min.  | dimensions (L x W x H)     | 360 x 160 x 130 mm  |
| total height      | 1,250 mm (49.2")          |                            | (14.2 x 6.3 x 5.1") |

Packaging  
cardboard box

Ref. No.:  
9626820