


G3H



-size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	kg/100m	REF.
-4	6	1/4	0.56	14.2	1250	8.8	5000	35.0	75	19	4G3H
-6	10	3/8	0.75	19.1	1125	7.9	4500	31.5	100	33	6G3H
-8	12	1/2	0.94	23.9	1000	7.0	4000	28.0	125	48	8G3H
-10	16	5/8	1.10	27.9	900	6.2	3600	24.8	140	57	10G3H
-12	19	3/4	1.25	31.8	750	5.2	3000	21.0	150	71	12G3H
-16	25	1	1.50	38.1	565	3.9	2260	15.8	200	92	16G3H
-20	31	1.1/4	1.75	44.5	375	2.6	1500	10.5	250	110	20G3H

RECOMMENDED FOR	High-temperature, low pressure hydraulic oil lines, anti-freeze solutions and water.
TUBE	NBR (Nitrile) based.
REINFORCEMENT	Two fibre braids.
COVER	CR (Chloroprene) based.
TEMPERATURE RANGE	-40°C to +135°C constant and +150°C intermittent. For water emulsions, etc. see Engineering and technical data page 292.
STANDARDS	Exceeds ISO 4079 R3. EN 854 R3. SAE 100R3.
COUPLINGS	-4 to -10: MegaCrimp; for replacement of crimped assemblies with larger inner diameter we recommend to use ACR MegaTech™.