


R605**Short Male-Female reducing (ISO 8434-6)****S**

Product number	Ø tube		Thread		Dimension			Weight kg/unit
	mm	inch	F	F1	L	L2	CH1	
R605-04-02	8-6	5/16"-1/4"	G 1/4	G 1/8	23	11	19	0,030
R605-06-02	10-6	3/8"-1/4"	G 3/8	G 1/8	21.5	12	22	0,036
R605-06-04	10-8	3/8"-5/16"	G 3/8	G 1/4	27	12	22	0,046
R605-08-04	12-8	1/2"-5/16"	G 1/2	G 1/4	25	14	27	0,061
R605-08-06	12-10	1/2"-3/8"	G 1/2	G 3/8	28.5	14	27	0,065
R605-12-04	20-8	3/4"-5/16"	G 3/4	G 1/4	27	16	32	0,098
R605-12-06	20-10	3/4"-3/8"	G 3/4	G 3/8	27	16	32	0,089
R605-12-08	20-12	3/4"-1/2"	G 3/4	G 1/2	33	16	32	0,072
R605-16-06	25-10	1"-3/8"	G 1	G 3/8	30	19	41	0,164
R605-16-08	25-12	1"-1/2"	G 1	G 1/2	31	19	41	0,161
R605-16-12	25-20	1"-3/4"	G 1	G 3/4	38	19	41	0,187
R605-20-12	32-20	1.1/4"-3/4"	G 1 1/4	G 3/4	34	20	50	0,270
R605-20-16	32-25	1.1/4"-1"	G 1 1/4	G 1	34	20	50	0,218
R605-24-12	38-20	1.1/2"-3/4"	G 1 1/2	G 3/4	39	22	55	0,417
R605-24-16	38-25	1.1/2"-1"	G 1 1/2	G 1	35	22	55	0,315
R605-24-20	38-32	1.1/2"-1.1/4"	G 1 1/2	G 1 1/4	45	22	55	0,349
R605-32-16	50-25	2"-1"	G 2	G 1	40	25	70	0,627
R605-32-20	50-32	2"-1.1/4"	G 2	G 1 1/4	42.5	25	70	0,584
R605-32-24	50-38	2"-1.1/2"	G 2	G 1 1/2	42.5	25	70	0,521