

Concrete, Plaster & Grout

EHK005

Plaster & Grout Spraying



Application

- For high-pressure spraying plaster, grout, sand, gypsum, and ready mixed concrete

Markets

- Construction
- Cement
- Swimming pool

Construction

Tube Reinforcement Abrasion resistant SBR rubber blend

High-tensile synthetic textile and anti-static copper wire

Cover Abrasion, ozone, and weather resistant pin-pricked SBR rubber blend

Colors Black (BK), Gray (GY), Yellow (YW)

Abrasion loss value acc. DIN53516 $\leq 60\text{mm}^3$

Operating temperature

-40°C to +70°C
(-40°F to +158°F)

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHK005-12BK	19.0	0.75	31.0	1.22	41.0	600	123.0	1800	90	3.54	0.54	0.36	61	200
EHK005-16BK	25.4	1.00	37.0	1.46	41.0	600	123.0	1800	120	4.72	0.65	0.44	61	200
EHK005-16ABK	25.4	1.00	38.0	1.50	41.0	600	123.0	1800	110	4.33	0.75	0.50	61	200
EHK005-19BK	30.0	1.18	44.0	1.73	41.0	600	123.0	1800	150	10.34	0.95	0.64	61	200
EHK005-20BK	32.0	1.25	46.0	1.81	41.0	600	123.0	1800	160	6.30	1.03	0.69	61	200
EHK005-22BK	35.0	1.38	49.0	1.93	41.0	600	123.0	1800	175	6.89	1.10	0.74	61	200
EHK005-24BK	38.0	1.50	54.0	2.13	41.0	600	123.0	1800	190	7.48	1.43	0.96	61	200
EHK005-28BK	44.5	1.75	61.0	2.40	41.0	600	123.0	1800	225	8.86	1.63	1.10	61	200
EHK005-32BK	50.8	2.00	68.0	2.68	41.0	600	123.0	1800	280	11.02	1.96	1.32	61	200
EHK005-38BK	60.0	2.36	80.0	3.15	41.0	600	123.0	1800	340	13.38	2.72	1.83	61	200
EHK005-40BK	63.5	2.50	83.5	3.29	41.0	600	123.0	1800	375	14.76	2.86	1.92	61	200
EHK005-42BK	65.0	2.56	85.0	3.35	41.0	600	123.0	1800	390	15.36	2.88	1.94	61	200
EHK005-44BK	70.0	2.76	90.0	3.54	41.0	600	123.0	1800	425	16.73	2.93	1.97	61	200
EHK005-48BK	76.2	3.00	96.2	3.79	41.0	600	123.0	1800	440	17.32	3.14	2.11	61	200
EHK005-64BK	101.6	4.00	122.0	4.80	41.0	600	123.0	1800	580	22.83	4.14	2.78	61	200
EHK005-80BK	127.0	5.00	155.0	6.10	41.0	600	123.0	1800	750	29.52	6.85	4.60	61	200