

# CEMO DT MOBIL Easy 200, 470 and 620 L PG 4

ADR CERTIFIED

**NEW**

**IMDG&RID**  
ADR certified transport



DT-Mobil EASY 620 L with electric pump, automatic nozzle and hinged lid

**DT-Mobil EASY with ADR certification** certified for transport under ADR, examination every 2 ½ years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b).\*\*\* Completely assembled.

Container:

- 200 L, 470 L or 620 L polyethylene, single-walled
- with hinged lid
- with crane eyes (470 L and 620 L)
- integral filler neck
- filler cap with vent and breather valves
- integral forklift pockets and handles
- integral recesses (200 L) or loops (470 L and 620 L) for securing with ratchet straps during transport

Pre-fitted pump:

- self-priming, pump 12 V or 24 V DC, 40 L/min, with automatic nozzle, 4 m dispensing hose DN 19 and 4 m electrical cable
- submersible pump CENTRI SP 30, 12 V, 30 L/min, extremely quiet, with automatic nozzle, 4 m dispensing hose DN 19 or DN25 (model 11919 and 11924) and 4 m cable
- hand pump 25 L/min, 2.7 m dispensing hose DN 19 and manual nozzle

\*\*\* Transport certification for all plastic IBCs is limited to a life of 5 years. The 200 L model is therefore also certified for transport for direct consumption under ADR 1.1.3.1 c).

DT-Mobil EASY 200 L with electric pump, automatic nozzle and hinged lid



See catalogue page 163 for suitable steel bund SW 600/2



## DT-MOBIL EASY WITH ADR CERTIFICATION

Description / capacity	Dimensions in cm (l x w x h)	Weight approx. kg	Order no.
200 L with hand pump, manual nozzle	80 x 62 x 61	26	10080
200 L with submersible pump CENTRI SP 30, extremely quiet, 12 V, 30 L/min, automatic nozzle	80 x 62 x 61	24	10735
200 L with pump 12 V, 40 L/min, automatic nozzle	80 x 62 x 61	28	10082
200 L with pump 24 V, 40 L/min, automatic nozzle	80 x 62 x 61	28	10112
470 L without pump, with quick coupling for vehicles with integrated suction pump	118 x 80 x 87	38	11917
470 L with pump 12 V, 40 L/min and automatic nozzle	118 x 80 x 87	45	11918
470 L with pump Cematic Duo 24/12V, 70/35 L/min and automatic nozzle	118 x 80 x 87	51	11919
620 L without pump, with quick coupling for vehicles with integrated suction pump	118 x 80 x 103	42	11922
620 L with pump 12 V, 40 L/min and automatic nozzle	118 x 80 x 103	48	11923
620 L with pump Cematic Duo 24/12V, 70/35 L/min and automatic nozzle	118 x 80 x 103	54	11924

★ Accessories see page 48.

\*\*\* Please note that ADR certification for all plastic IBCs is limited to a period of 5 years.