



Composition: TUBE:BLACK, SMOOTH, SPECIAL SYNTHETIC RUBBER WITH VERY LOW GAS PERMEATION
BARRIER: POLYAMIDE LAYER, RESISTANT TO GAS PERMEATION
REINFORCEMENT: 2 HIGH TENSILE SYNTHETIC TEXTILE SPIRAL LAYER.
COVER: BLACK, SPECIAL SYNTHETIC RUBBER, RESISTANT TO HIG

Working temperature: -30° C +125° C.

APPLICATION: FOR THE TRANSFER OF R134a-R404-R410 GAS AND LIQUID, IN AIR CONDITIONING SYSTEMS FOR AUTOMOTIVE INDUSTRY.

Part nº	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MSB2506	5/16"	8	19	35	508	137	1.987	55	0.285
MSB2508	13/32"	10.3	23	35	508	137	1.987	75	0.405
MSB2510	1/2"	13	25,4	35	508	137	1.987	90	0.460
MSB2512	5/8"	16	28,6	35	508	137	1.987	110	0.545

SAE J2064 TYPE C