

DKJ-JIS 90° DKJ-JIS 90°


Whitworth Rohrgewinde (BSPP), zylindrisch

Abdichtung: Dichtkegelanschluss mit 60° Innenkonus und gecrimpter Mutter

Whitworth pipe thread (BSPP), cylindric

Sealing: 60° inner cone and crimped nut

Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
-04	6	1/4"	G 1/4"-19	23	21,4	52	19	424 97 06 32
-04	6	1/4"	G 3/8"-19	23	27,7	52	19	424 97 06 33
-06	10	3/8"	G 3/8"-19	33	32,3	63,5	22	424 97 10 33
-06	10	3/8"	G 1/2"-14	33	33,2	63,5	27	424 97 10 34
-08	12	1/2"	G 1/2"-14	39,5	37,7	72	27	424 97 12 34
-12	19	3/4"	G 3/4"-14	57	54	98	32	424 97 20 36
-16	25	1"	G 1"-11	60	66,7	115	40	424 97 25 37



AG-JIS AG-JIS

Whitworth Rohrgewinde (BSPP), zylindrisch

Abdichtung: Außengewindenippel mit 60° Außenkonus

Whitworth pipe thread (BSPP), cylindric

Sealing: 60° cone connection with external cone

Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
-04	6	1/4"	G 1/4"-19	31	59,3	19	424 99 00 10
-06	10	3/8"	G 3/8"-19	32	62	22	424 99 00 13
-06	10	3/8"	G 1/2"-14	36,6	66,5	27	424 99 00 14
-08	12	1/2"	G 1/2"-14	33,4	66,1	27	424 99 00 15
-12	19	3/4"	G 3/4"-14	37,5	78	32	424 99 00 17

