



MC2130AZ39AS10000100002ABABAAB, MC2130AZ39AS10000100002ABABAAB

631AG00026A

Where to buy

Product specifications

Characteristic	Value
Model code	MC2130AZ39AS10000100002ABABAAB
Motor Series	XL2 Series
Valve system	Disc valve with valve drive
Orbital gearwheel set type	Geroler
Motor size	130
Geometric displacement [cm3/r [in3/r]]	130.5 [7.96]
Motor type	Short
Motor function	Standard
Mounting flange type	4 Bolt - Short
Mounting flange dimension [pilot dia x height, bolt circle dia, hole [mm [inch]]]	100.0 x 6.0, 125.0, 11.0 [3.94 x 0.24, 4.92, 0.43]
Shaft type	None
Shaft dimension	n/a
Shaft Key	n/a
Main port thread type	BSP
Main port style	Sideport - staggered
Main port dimension	G 1/2, 2 x M10 x 1.5-6H block mounting threads
Drain Port Dimension	G 1/4 - Spec. Component
Brake Release Port Dimension	n/a
Painted	Yes



Characteristic	Value
Paint information	Painted, Black
Special features hardware	Spec. Component
Special Features Assembly	Direction of rotation
Dust seal	n/a
Shaft Seal	n/a
Seal Kit	No data available
Front bearing type	n/a
Rear bearing type	n/a
Orbital gearwheel set	Standard
Check valve function	Yes
Hydraulic valve function	None
Sensor	None
Packaging	Single pack
Name Tag	Danfoss name tag
Design code	2
DG Indicator Profile	Not relevant for dangerous goods

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)