

Suction & Discharge

EHW009

Heavy Duty Water Suction & Discharge

**Application**

- For suction and discharge of water

Markets

- Construction
- Industrial

Construction

Tube SBR rubber blend

Reinforcement

High-tensile synthetic textile and dual steel helical wire

Cover Abrasion and weather resistant SBR rubber blend

Color Black

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Vacuum		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kPa	in/Hg	kg/m	lbs/ft	mtr	ft
EHW009-12BK	19.0	0.75	29.0	1.14	17.2	250	52.0	750	70	2.76	92.0	28	0.57	0.38	61	200
EHW009-16BK	25.4	1.00	35.0	1.38	17.2	250	52.0	750	100	3.94	92.0	28	0.72	0.48	61	200
EHW009-20BK	31.8	1.25	42.0	1.65	17.2	250	52.0	750	125	4.92	92.0	28	0.92	0.62	61	200
EHW009-24BK	38.1	1.50	50.0	1.97	17.2	250	52.0	750	150	5.91	92.0	28	1.34	0.90	61	200
EHW009-28BK	44.5	1.75	57.5	2.26	17.2	250	52.0	750	180	7.09	92.0	28	1.74	1.17	61	200
EHW009-32BK	50.8	2.00	64.0	2.52	17.2	250	52.0	750	240	9.45	92.0	28	1.92	1.29	61	200
EHW009-40BK	63.5	2.50	76.5	3.01	17.2	250	52.0	750	300	11.81	92.0	28	2.47	1.66	61	200
EHW009-44BK	70.0	2.75	84.0	3.31	17.2	250	52.0	750	340	13.39	92.0	28	2.79	1.87	61	200
EHW009-48BK	76.2	3.00	90.0	3.54	17.2	250	52.0	750	380	14.96	92.0	28	3.05	2.05	61	200
EHW009-64BK	101.6	4.00	118.0	4.65	17.2	250	52.0	750	500	19.69	92.0	28	4.86	3.26	61	200
EHW009-80BK	127.0	5.00	144.0	5.67	17.2	250	52.0	750	650	25.59	92.0	28	6.34	4.26	61	200
EHW009-96BK	152.4	6.00	173.0	6.81	17.2	250	52.0	750	850	33.46	92.0	28	9.39	6.31	61	200
EHW009-128BK	203.2	8.00	228.0	8.98	17.2	250	52.0	750	1200	47.24	80.0	24	14.88	10.00	61	200
EHW009-160BK	254.0	10.00	284.0	11.18	17.2	250	52.0	750	1600	62.99	80.0	24	20.76	13.95	61	200
EHW009-192BK	304.8	12.00	339.0	13.35	17.2	250	52.0	750	1900	74.80	80.0	24	28.48	19.14	61	200