

## Description

## Item No.

### HP 350-V-EX Lever Operated Barrel Pump

designed for drums of 50 litre to 200 litre capacity, with grounding clamp, steel telescopic suction tube, variable 450 mm to 860 mm, body of zinc plated steel, 2" and 1 1/2" drum adapter, removable, angled spout, seals made of VITON, suitable for petrol and 2-stroke mixture

flow rate: 350 cc per stroke

HP 350-V-EX

34 636 32



### RP 100-EX Aluminium Rotary Pump

includes 1.5 m delivery hose, ball valve and nozzle for gear oil, 2 chamber vane pump with grounding clamp, metal suction tube 1" / 1.000 mm long, 1" foot valve male/female with seal, designed for drums up to 200 litre, 2" bung adaptor, suitable for petrol and 2-stroke mixture

flow rate: 250 cc per revolution

RP 100-EX

34 611 26



### RP 100-EX Aluminium Rotary Pump with meter DIGIMET M80-VITON

includes 1.5 m delivery hose, ball valve and nozzle for gear oil, 2 chamber vane pump with grounding clamp, metal suction tube 1" / 1.000 mm, 1" foot valve male/female with seal, flow meter DIGIMET M80, Viton, accuracy ±1% (at 16-80 l/min), designed for drums up to 200 litres, 2" bung adaptor, suitable for petrol and 2-stroke mixture

flow rate: 250 cc per revolution

RP 100-EX with DIGIMET M80-VITON

34 611 02



### Delivery Hose EX DN 20 - 1.5 m

3/4" male ends, conductive and petrol resistant

Delivery hose EX DN 20 - 1.5 m

34 620 24



### Ball Valve Nozzle Assembly

ball valve with nozzle for gear oil, thread: R3/4" female

Ball valve nozzle assembly

34 620 48

