


M FIRG17QV 1 BSP

Codice articolo: 800900113 / Male



Body size 3/4"	Valving style Flat face
Interchange ISO 16028	Sealing FKM (VITON)
Connection system Push	Disconnection system Pull back the sleeve
Material Carbon steel + Stainless steel (AISI 303)	Treatment QPQ
Locking mechanism Locking ball + Safety lock	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure No
Temperature -15 / +180 °C; +5 / +356 °F	Applications Oil & Gas, Industry, Cooling, Chemical & Food Industry

Performance

METRIC

Max. Flow suggested (l/min)	200
Connect force (N)	220
Disconnect force (N)	70
Spillage (ml)	0.03
Operating pressure - uncoupled (mpa)	25
Burst pressure - coupled (mpa)	100
ISO DN (mm)	19
Burst pressure - uncoupled (mpa)	90
Max. Operating pressure - coupled (Mpa)	25

Dimensions

METRIC

Port (A)	1"
Overall length M+F (mm)	153,5
Length (mm)	82,3
Max. diameter (mm)	50
Weight (kg)	0,4

Related products

Product code	Typology	Product name
800900112	Femmina	F FIRG17QV 1 BSP

Spare kits

Product code	Product name
815700253	SPARE KIT OR VITON+BK M FF 34

Caps

Product code	Product name
815103013	PLASTIC CAP M FF34 BLACK *
815102013	PLASTIC CAP M FF34 BLUE *
815104013	PLASTIC CAP M FF34 GREEN *
815110031	PLASTIC CAP M FF34 MAGENTA *
815107031	PLASTIC CAP M FF34 ORANGE *
815105013	PLASTIC CAP M FF34 WHITE *
815101013	PLASTIC CAP M FF34 YELLOW *
816005011	ALUMINUM CAP M FF34 NATURAL
815100013	PLASTIC CAP M FF34 RED

*Product available upon request