

Beverage Suction and Discharge

EHT200

Bosphorus Non-toxic Steel Spiral



Application

- For suction & delivery of water, mineral, fruit juices, liquids, etc.

Markets

- Food & beverage
- Shipyards
- Buildings
- Agriculture
- Industrial machineries

Construction

Tube Strong, flexible and smooth non-toxic plasticized PVC
FDA compliant

Reinforcement

Shock resistant galvanized steel spiral wire

Color Clear

Certifications

FDA compliant

Operating temperature

-5°C to +60°C
(+23°F to +140°F)

Number	Hose I.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Vacuum		Weight		Length	
	mm	in	bar	psi	bar	psi	mm	in	kPa	in/Hg	kg/m	lbs/ft	mtr	ft
EHT200-08	12.7	0.50	7.0	100	21.0	305	25.0	0.98	88.3	26.0	0.18	0.12	91.4	300
EHT200-10	15.9	0.62	6.0	85	18.0	261	35.0	1.38	88.3	26.0	0.23	0.15	91.4	300
EHT200-12	19.0	0.75	5.0	75	15.0	218	50.0	1.97	88.3	26.0	0.34	0.23	91.4	300
EHT200-16	25.4	1.00	5.0	75	15.0	218	60.0	2.36	88.3	26.0	0.51	0.34	91.4	300
EHT200-20	31.8	1.25	4.3	62	13.0	189	75.0	2.95	88.3	26.0	0.65	0.44	91.4	300
EHT200-24	38.1	1.50	4.0	60	12.0	174	90.0	3.54	88.3	26.0	0.80	0.54	45.7	150
EHT200-32	50.8	2.00	3.0	40	9.0	131	125.0	4.92	78.5	23.0	1.20	0.81	45.7	150
EHT200-40	63.5	2.50	2.3	33	7.0	102	150.0	5.91	68.7	20.0	1.95	1.31	45.7	150
EHT200-48	76.2	3.00	2.0	29	6.0	87	195.0	7.68	68.7	20.0	2.50	1.68	45.7	150
EHT200-64	101.6	4.00	2.0	29	6.0	87	300.0	11.81	58.9	17.0	3.40	2.28	30.5	100
EHT200-80	127.0	5.00	2.0	29	6.0	87	385.0	15.16	58.9	17.0	4.70	3.16	30.5	100
EHT200-96	152.4	6.00	2.0	29	6.0	87	460.0	18.11	58.9	17.0	6.35	4.27	30.5	100