


UNF MB

Male SAE 'O' ring boss. SAE J1926/3.

ISO 11926/3 light duty (L series).



							
D				A	B	H	REF.
-size	DN	"		mm	mm	mm	G
-4	6	1/4	7/16" - 20 UNF	50.5	24.5	14.3	4G4MB
-4	6	1/4	1/2" - 20 UNF	50.5	24.5	15.9	4G5MB
-4	6	1/4	9/16" - 18 UNF	52.0	26.0	17.5	4G6MB
-6	10	3/8	9/16" - 18 UNF	56.0	28.1	17.5	6G6MB
-6	10	3/8	3/4" - 16 UNF	58.0	30.1	22.2	6G8MB
-6	10	3/8	7/8" - 14 UNF	56.5	28.6	25.4	6G10MB
-6	10	3/8	1.1/16" - 12 UN	61.5	33.6	31.8	6G12MB
-8	12	1/2	3/4" - 16 UNF	67.0	29.5	22.2	8G8MB
-8	12	1/2	7/8" - 14 UNF	68.0	30.5	25.4	8G10MB
-8	12	1/2	1.1/16" - 12 UN	74.0	36.5	31.8	8G12MB
-10	16	5/8	3/4" - 16 UNF	72.0	34.5	23.8	10G8MB
-10	16	5/8	7/8" - 14 UNF	72.0	34.5	25.4	10G10MB
-10	16	5/8	1.1/16" - 12 UN	76.0	38.5	31.8	10G12MB
-12	20	3/4	1.1/16" - 12 UN	84.5	33.5	31.8	12G12MB
-12	20	3/4	1.3/16" - 12 UN	84.0	33.0	34.9	12G14MB
-12	20	3/4	1.5/16" - 12 UN	87.5	36.5	38.1	12G16MB
-16	25	1	1.3/16" - 12 UN	96.0	39.2	34.9	16G14MB
-16	25	1	1.5/16" - 12 UN	97.5	40.7	38.1	16G16MB
-20	32	1.1/4	1.5/8" - 12 UN	99.0	40.0	47.6	20G20MB

Unless otherwise stated the coupling meets the pressure rating requirements of the respective international standard.