

HIGH PRESSURE HOSES

With UMETA's hoses, you establish an optimal connection between your grease gun and the lubricating spot. Available in two versions and lengths, either without nozzle, or already assembled with the UMETA nozzle of your choice.

360/LN



inner Ø	4.0 mm (0.16")
outer Ø	10.2 mm (0.4")
burst pressure	1,000 bar / 14,500 PSI
testing pressure	800 bar / 11,600 PSI
operating pressure max.	400 bar / 5,800 PSI

Type	Connection	Connector	Length	Ref. No.:
360/LN	M 10 x 1	without nozzle	300 mm (12")	V000145
340/GLN	M 10 x 1	hydraulic coupler H	300 mm (12")	V000039
330/LN	M 10 x 1	button head coupler M 4	300 mm (12")	V000366
350/LN	M 10 x 1	button head coupler M 1 + T 1	300 mm (12")	V000283
354/LN	M 10 x 1	button head coupler M 22	300 mm (12")	V000318
360/LN	G 1/8	without nozzle	300 mm (12")	V000130
340/GLN	G 1/8	hydraulic coupler H	300 mm (12")	V000108
330/LN	G 1/8	button head coupler M 4	300 mm (12")	V001048
350/LN	G 1/8	button head coupler M 1 + T 1	300 mm (12")	V000223
354/LN	G 1/8	button head coupler M 22	300 mm (12")	V000650
360/LN	1/8" NPT	without nozzle	300 mm (12")	V000109
340/GLN	1/8" NPT	hydraulic coupler H	300 mm (12")	V000326
330/LN	1/8" NPT	button head coupler M 4	300 mm (12")	V001662
350/LN	1/8" NPT	button head coupler M 1 + T 1	300 mm (12")	V000682
354/LN	1/8" NPT	button head coupler M 22	300 mm (12")	V000683

360/L



inner Ø	4.8 mm (0.19")
outer Ø	12.5 mm (0.5")
burst pressure	1,650 bar / 23,925 PSI
testing pressure	800 bar / 11,600 PSI
operating pressure max.	415 bar / 6,000 PSI

Type	Connection	Connector	Length	Ref. No.:
360/L	M 10 x 1	without nozzle	300 mm (12")	V000282
340/GL	M 10 x 1	hydraulic coupler H	300 mm (12")	V000200
330/L	M 10 x 1	slide coupler M 4	300 mm (12")	V001206
350/L	M 10 x 1	slide coupler M 1 + T 1	300 mm (12")	V000311
354/L	M 10 x 1	slide coupler M 22	300 mm (12")	V000653
360/L	G 1/8	without nozzle	300 mm (12")	V000410
340/GL	G 1/8	hydraulic coupler H	300 mm (12")	V000042
330/L	G 1/8	slide coupler M 4	300 mm (12")	V001208
350/L	G 1/8	slide coupler M 1 + T 1	300 mm (12")	V000741
354/L	G 1/8	slide coupler M 22	300 mm (12")	V000761
360/L	1/8" NPT	without nozzle	300 mm (12")	V000521
340/GL	1/8" NPT	hydraulic coupler H	300 mm (12")	V000686
330/L	1/8" NPT	slide coupler M 4	300 mm (12")	V001672
350/L	1/8" NPT	slide coupler M 1 + T 1	300 mm (12")	V000687
354/L	1/8" NPT	slide coupler M 22	300 mm (12")	V000688

Please be aware of smallest allowable bending radius.

ATTENTION: NEVER FOLD!

High pressure hose Ø 11 mm (0.43")

· DIN 1283

temperature range	-20°C – +60°C (-4 °F - +140 °F)
allowed bending radius max.	35 mm (1.37")
inner layer	polyethylene
reinforcement	1 polyester insert
outer layer	polyamide

Type	Connection	Connector	Length	Ref. No.:
362/LN	M 10 x 1	without nozzle	500 mm (20")	V000312
342/GLN	M 10 x 1	hydraulic coupler H	500 mm (20")	V000041
332/LN	M 10 x 1	button head coupler M 4	500 mm (20")	V000940
352/LN	M 10 x 1	button head coupler M 1 + T 1	500 mm (20")	V000298
356/LN	M 10 x 1	button head coupler M 22	500 mm (20")	V000394
362/LN	G 1/8	without nozzle	500 mm (20")	V000323
342/GLN	G 1/8	hydraulic coupler H	500 mm (20")	V000288
332/LN	G 1/8	button head coupler M 4	500 mm (20")	V001049
352/LN	G 1/8	button head coupler M 1 + T 1	500 mm (20")	V000651
356/LN	G 1/8	button head coupler M 22	500 mm (20")	V000652
362/LN	1/8" NPT	without nozzle	500 mm (20")	V000328
342/GLN	1/8" NPT	hydraulic coupler H	500 mm (20")	V000327
332/LN	1/8" NPT	button head coupler M4	500 mm (20")	V001663
352/LN	1/8" NPT	button head coupler M 1 + T 1	500 mm (20")	V000684
356/LN	1/8" NPT	button head coupler M 22	500 mm (20")	V000685

high pressure hose 2 SN Ø 13 mm (½")

· DIN 1283

temperature range:	-40°C – +100°C (-40 °F - +212 °F)
allowed bending radius max.:	90 mm (3.5")
inner layer	polyethylene
reinforcement	double steel wire braid
outer layer	synth. rubber



Type	Connection	Connector	Length	Ref. No.:
362/L	M 10 x 1	without nozzle	500 mm (20")	V000297
342/GL	M 10 x 1	hydraulic coupler H	500 mm (20")	V000294
332/L	M 10 x 1	slide coupler M 4	500 mm (20")	V001207
352/L	M 10 x 1	slide coupler M 1 + T 1	500 mm (20")	V000475
356/L	M 10 x 1	slide coupler M 22	500 mm (20")	V000332
362/L	G 1/8	without nozzle	500 mm (20")	V000471
342/GL	G 1/8	hydraulic coupler H	500 mm (20")	V000496
332/L	G 1/8	slide coupler M 4	500 mm (20")	V001209
352/L	G 1/8	slide coupler M 1 + T 1	500 mm (20")	V001210
356/L	G 1/8	slide coupler M 22	500 mm (20")	V001020
362/L	1/8" NPT	without nozzle	500 mm (20")	V000465
342/GL	1/8" NPT	hydraulic coupler H	500 mm (20")	V000689
332/L	1/8" NPT	slide coupler M 4	500 mm (20")	V001673
352/L	1/8" NPT	slide coupler M 1 + T 1	500 mm (20")	V000490
356/L	1/8" NPT	slide coupler M 22	500 mm (20")	V000691