


Thread Adaptor SRS-20



Ordering Codes

SRS-20*-M12x1.5*-B*-C*-W3

* Type	Thread Adaptor	SRS
* Series	STAUFF Test 20 (All sizes)	-20
* Port Connection	acc. to dimension table	-M12x1.5
* Seal Material	NBR (Buna-N®) FKM (Viton®) EPDM Seal Type B and D	-B -V -E none
* Seal Type	Metal Joint Type B Elastomeric Sealing Type C Taper Type D O-ring Type E	-B -C -D -E
* Material Code	Steel, zinc/nickel-plated Stainless Steel V2A - 1.4305 (AISI 303) Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W3 -W4 -W5

Seal Type



Metal Joint Type B



Elastomeric Sealing Type C



Taper Type D¹



O-ring Type E

For further information on Seal Types,
please see page 74-77.

Thread T	Seal Type	Dimensions (mm/in)			Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
		h1	h2	Hex		
M10 x 1	Type B	15,5 .61	8,5 .33	17 .67	2,40 5.28	SRS-20-M10x1-B-W3
M12 x 1,5		15 .59	12 .47	19 .75	3,20 7.04	SRS-20-M12x1.5-B-W3
M14 x 1,5		15 .59	12 .47	19 .75	3,70 8.14	SRS-20-M14x1.5-B-W3
M16 x 1,5		8 .31	12 .47	22 .87	2,80 6.16	SRS-20-M16x1.5-B-W3
M18 x 1,5		15 .59	12 .47	24 .94	6,20 13.64	SRS-20-M18x1.5-B-W3
M22 x 1,5		10,5 .41	14 .55	27 1.06	7,20 15.84	SRS-20-M22x1.5-B-W3
G1/8		15,5 .61	8 .31	17 .67	2,50 5.50	SRS-20-G1/8-B-W3
G1/4		15 .59	12 .47	19 .75	3,50 7.70	SRS-20-G1/4-B-W3
G3/8		10,5 .41	12 .47	22 .87	3,80 8.36	SRS-20-G3/8-B-W3
G1/2		10,5 .41	14 .55	27 1.06	6,60 14.52	SRS-20-G1/2-B-W3
M12 x 1,5	Type C	15 .59	12 .47	19 .75	3,30 7.28	SRS-20-M12x1.5-B-C-W3
M14 x 1,5		15 .59	12 .47	19 .75	3,80 8.38	SRS-20-M14x1.5-B-C-W3
M18 x 1,5		15 .59	12 .47	24 .94	6,70 8.16	SRS-20-M18x1.5-B-C-W3
G1/8		16 .63	8 .31	17 .67	2,90 3.39	SRS-20-G1/8-B-C-W3
G1/4		15 .59	12 .47	19 .75	3,60 7.92	SRS-20-G1/4-B-C-W3
G3/8		10,5 .41	12 .47	22 .87	3,70 8.14	SRS-20-G3/8-B-C-W3
G1/2		10,5 .41	14 .55	27 1.06	6,80 14.96	SRS-20-G1/2-B-C-W3
R1/4 K	Type D¹	13 .51	12 .47	17 .67	3,20 7.04	SRS-20-R1/4K-D-W3
R3/8 K		13 .51	14 .55	19 .75	4,10 9.02	SRS-20-R3/8K-D-W3
R1/2 K		8 .31	19 .75	22 .87	5,80 12.76	SRS-20-R1/2K-D-W3
1/4 NPT		10 .39	15 .59	17 .67	2,39 5.26	SRS-20-1/4NPT-D-W3
1/2 NPT		8 .31	20 .79	22 .87	5,83 12.83	SRS-20-1/2NPT-D-W3
7/16-20 UNF	Type E	9 .35	9,1 .36	17 .67	2,30 5.06	SRS-20-7/16UNF-B-E-W3
1/2-20 UNF		15 .59	9,2 .36	17 .67	2,50 5.50	SRS-20-1/2UNF-B-E-W3
9/16-18 UNF		15,5 .61	10 .39	19 .75	3,60 7.92	SRS-20-9/16UNF-B-E-W3
7/8-14 UNF		11 .43	16 .63	27 1.06	2,50 5.51	SRS-20-7/8UNF-B-E-W3
M14 x 1,5		14,5 .57	11 .43	19 .75	3,90 8.59	SRS-20-M14x1.5-B-E-W3
M16 x 1,5		8,5 .33	12,5 .49	22 .87	3,20 7.04	SRS-20-M16x1.5-B-E-W3
M22 x 1,5		10 .39	15 .59	27 1.06	7,20 15.87	SRS-20-M22x1.5-B-E-W3
M27 x 2		10 .39	18,5 .73	32 1.26	7,00 15.43	SRS-20-M27x2-B-E-W3

¹ Suitable liquid / plastic sealant required.

Dimensional drawings: All dimensions in mm (in).

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.