

TW - Kupplung Typ MK (Spannringhebel)

Female coupler type MK (lever)

Raccord type MK (levier)

TW- Acople hembra tipo MK (palanca)

TW Gniazdo typ MK (Dźwignia pierścienia mocującego)

TW - Tipo MK senza corona (leva)



Part-No.	Material	WP	Dimension	Thread	Price
2MKSS	SS 1.4408	16 bar	DN50	G2"	
3MKSS	SS 1.4408	16 bar	DN80	G3"	

TW-Kupplung Typ MK (nur Spannringhebel mit 45° Hebel)

Female coupler type MK (only lever with 45° lever)

Raccord type MK (uniquement levier 45°)

TW-Acople hembra tipo MK (sin corona con palanca de 45°)

TW Gniazdo typ MK (Dźwignia pierścienia mocującego z 45 klamką)

TW-Tipo MK senza corona (leva singola leva a 45°)

**NEW**

Part-No.	Material	WP	Dimension	Thread	Price
2MKSS45	SS 1.4408	16 bar	DN50	G2"	

TW-Kupplung Typ MK mit BSPP – Innengewinde (Komplett mit 90° Hebel)

mit CSM Lippendichtung und PTFE Gewindedichtung

Female coupler type MK BSPP female thread (with 90° lever) - CSM lip gasket PTFE thread-gasket

Raccord type MK taraudé femelle BSPP (levier 90°) - Joint CSM pour raccord - Joint de filetage PTFE

TW-Acople hembra tipo MK con rosca hembra BSPP (con palanca de 90°) - Junta labial CSM Junta de rosca de PTFE

TW Gniazdo typ MK z gwintem wewnętrznym BSPP (z 90° klamką) - Uszczelka profilowa CSM Uszczelka o-ring PTFE

TW-Tipo MK filettato femmina BSPP (leva a 90°) - CSM Guarnizione filettato PTFE



Part-No.	Material	WP	Dimension	Thread	Price
3MKS90	SS 1.4408	16 bar	DN80	G3"	

