



BSL type 510 for 1 line




NORMAFIX® BSL TYPE 510 FOR 1 LINE (in accordance with DIN 72571)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 510 1 x 4	4	3/16"	18	9	4.8	1	0510 8980 104
	BSL 510 1 x 5	5	3/16"	18.5	9	4.8	1	0510 8980 105
	BSL 510 1 x 6	6	1/4"	20	10	4.8	1	0510 8980 106
	BSL 510 1 x 7	7	1/4"	20.5	10	4.8	1	0510 8980 107
	BSL 510 1 x 8	8	5/16"	22	11	4.8	1	0510 8980 108
	BSL 510 1 x 9	9	3/8"	22.5	11	4.8	1	0510 8980 109
12	BSL 510 1 x 10	10	3/8"	23	11	4.8	1	0510 8980 110
	BSL 510 1 x 11	11	7/16"	30	15	5.8	1.5	0510 8980 111
	BSL 510 1 x 12	12	1/2"	30.5	16	5.8	1.5	0510 8980 112
	BSL 510 1 x 15	15	9/16"	34	18	5.8	1.5	0510 8980 115
	BSL 510 1 x 16	16	5/8"	35	18	5.8	1.5	0510 8980 116
	BSL 510 1 x 18	18	11/16"	35.5	18	7	1.5	0510 8980 118
	BSL 510 1 x 20	20	13/16"	37.5	19	7	1.5	0510 8980 120
	BSL 510 1 x 22	22	7/8"	39.5	20	7	1.5	0510 8980 122
BSL 510 1 x 24	24	15/16"	41.5	21	7	1.5	0510 8980 124	

BSL type 510 for 2 lines



NORMAFIX® BSL TYPE 510 FOR 2 LINES (in accordance with DIN 72571)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 510 2 x 4	4	3/16"	22.5	11	4.8	1	0510 8980 204
	BSL 510 2 x 5	5	3/16"	24	11.5	4.8	1	0510 8980 205
	BSL 510 2 x 6	6	1/4"	26.5	13	4.8	1	0510 8980 206
	BSL 510 2 x 7	7	1/4"	28	13.5	4.8	1	0510 8980 207
	BSL 510 2 x 8	8	5/16"	30.5	15	4.8	1	0510 8980 208
	BSL 510 2 x 10	10	3/8"	33.5	16	4.8	1	0510 8980 210
12	BSL 510 2 x 12	12	1/2"	43	22	5.8	1.5	0510 8980 212
	BSL 510 2 x 15	15	9/16"	49	25.3	5.8	1.5	0510 8980 215


BSL type 512 for 1 line



NORMAFIX® BSL TYPE 512 FOR 1 LINE (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 1 x 4	4	3/16"	29	17	4.8	1	0512 8980 104
	BSL 512 1 x 5	5	3/16"	30	18	4.8	1	0512 8980 105
	BSL 512 1 x 6	6	1/4"	32	20	4.8	1	0512 8980 106
	BSL 512 1 x 7	7	1/4"	32	20	4.8	1	0512 8980 107
	BSL 512 1 x 8	8	5/16"	34	22	4.8	1	0512 8980 108
	BSL 512 1 x 10	10	3/8"	34	22	4.8	1	0512 8980 110
12	BSL 512 1 x 12	12	1/2"	46	32	5.8	1.5	0512 8980 112
	BSL 512 1 x 15	15	9/16"	50	36	5.8	1.5	0512 8980 115
	BSL 512 1 x 18	18	11/16"	50	36	7	1.5	0512 8980 118
	BSL 512 1 x 20	20	13/16"	52	38	7	1.5	0512 8980 120
	BSL 512 1 x 22	22	7/8"	54	40	7	1.5	0512 8980 122


BSL – VERSIONS

BSL type 512 for 2 lines



NORMAFIX® BSL TYPE 512 FOR 2 LINES (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 2 x 4	4	3/16"	33	21	4.8	1	0512 8980 204
	BSL 512 2 x 5	5	3/16"	35	23	4.8	1	0512 8980 205
	BSL 512 2 x 6	6	1/4"	38	26	4.8	1	0512 8980 206
	BSL 512 2 x 7	7	1/4"	39	27	4.8	1	0512 8980 207
	BSL 512 2 x 8	8	5/16"	42	30	4.8	1	0512 8980 208
	BSL 512 2 x 10	10	3/8"	44	32	4.8	1	0512 8980 210
12	BSL 512 2 x 12	12	1/2"	58	44	5.8	1.5	0512 8980 212
	BSL 512 2 x 15	15	9/16"	66	52	5.8	1.5	0512 8980 215
	BSL 512 2 x 18	18	11/16"	69	55	7	1.5	0512 8980 218
	BSL 512 2 x 20	20	13/16"	73	59	7	1.5	0512 8980 220
	BSL 512 2 x 22	22	7/8"	77	63	7	1.5	0512 8980 222

BSL type 512 for 3 lines



NORMAFIX® BSL TYPE 512 FOR 3 LINES (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 3 x 4	4	3/16"	39	27	4.8	1	0512 8980 304
	BSL 512 3 x 5	5	3/16"	41	29	4.8	1	0512 8980 305
	BSL 512 3 x 6	6	1/4"	45	33	4.8	1	0512 8980 306
	BSL 512 3 x 7	7	1/4"	47	35	4.8	1	0512 8980 307
	BSL 512 3 x 8	8	5/16"	51	39	4.8	1	0512 8980 308
	BSL 512 3 x 10	10	3/8"	55	43	4.8	1	0512 8980 310
12	BSL 512 3 x 12	12	1/2"	71	57	5.8	1.5	0512 8980 312
	BSL 512 3 x 15	15	9/16"	81	67	5.8	1.5	0512 8980 315
	BSL 512 3 x 18	18	11/16"	87	73	7	1.5	0512 8980 318
	BSL 512 3 x 20	20	13/16"	93	79	7	1.5	0512 8980 320
	BSL 512 3 x 22	22	7/8"	99	85	7	1.5	0512 8980 322

BSL type 512 for 4 lines



NORMAFIX® BSL TYPE 512 FOR 4 LINES (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 4 x 4	4	3/16"	29	17	4.8	1	0512 8980 404
	BSL 512 4 x 5	5	3/16"	30	18	4.8	1	0512 8980 405
	BSL 512 4 x 6	6	1/4"	32	20	4.8	1	0512 8980 406
	BSL 512 4 x 7	7	1/4"	32	20	4.8	1	0512 8980 407
	BSL 512 4 x 8	8	5/16"	34	22	4.8	1	0512 8980 408
	BSL 512 4 x 10	10	3/8"	34	22	4.8	1	0512 8980 410
12	BSL 512 4 x 12	12	1/2"	46	32	5.8	1.5	0512 8980 412
	BSL 512 4 x 15	15	9/16"	50	36	5.8	1.5	0512 8980 415
	BSL 512 4 x 18	18	11/16"	50	36	7	1.5	0512 8980 418
	BSL 512 4 x 20	20	13/16"	52	38	7	1.5	0512 8980 420
	BSL 512 4 x 22	22	7/8"	54	40	7	1.5	0512 8980 422

## BSL type 512 for 5 lines



NORMAFIX® BSL TYPE 512 FOR 5 LINES (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 5 x 4	4	3/16"	48	36	4.8	1	0512 8980 504
	BSL 512 5 x 5	5	3/16"	53	41	4.8	1	0512 8980 505
	BSL 512 5 x 6	6	1/4"	57	45	4.8	1	0512 8980 506
	BSL 512 5 x 7	7	1/4"	63	51	4.8	1	0512 8980 507
	BSL 512 5 x 8	8	5/16"	68	56	4.8	1	0512 8980 508
	BSL 512 5 x 10	10	3/8"	77	65	4.8	1	0512 8980 510
12	BSL 512 5 x 12	12	1/2"	95	81	5.8	1.5	0512 8980 512

## BSL type 512 for 6 lines



NORMAFIX® BSL TYPE 512 FOR 6 LINES (in accordance with DIN 72573)								
Width b in mm	Designation	Clamping ranges		l <sub>1</sub> in mm	l <sub>2</sub> in mm	Bore hole in mm d	Mat. thickness in mm s	W1 Product No.
		in mm	in inches					
10	BSL 512 6 x 4	4	3/16"	52	40	4.8	1	0512 8980 604
	BSL 512 6 x 5	5	3/16"	58	46	4.8	1	0512 8980 605
	BSL 512 6 x 6	6	1/4"	64	52	4.8	1	0512 8980 606
	BSL 512 6 x 7	7	1/4"	72	60	4.8	1	0512 8980 607
	BSL 512 6 x 8	8	5/16"	76	64	4.8	1	0512 8980 608
	BSL 512 6 x 10	10	3/8"	90	78	4.8	1	0512 8980 610