

Description

Item No.

safeLOCK Hydraulic Safety Coupler

with 4-jaws made of high-strength metal, shaft length 51 mm

safeLOCK, M10x1  32 455 04

safeLOCK, R1/8"  32 456 03

safeLOCK, M10x1  32 455 11

safeLOCK, R1/8"  32 456 10



safeLOCK-L Hydraulic Safety Coupler

with a shaft length of 81 mm (e. g. for driveshafts)

safeLOCK-L, M10x1  32 457 02

safeLOCK-L, R1/8"  32 458 01



4-Jaw Hydraulic Coupler

heavy duty quality coupler, DIN 1283, for grease fittings DIN 71412, with machined and hardened jaws for optimal sealing and long lifetime, hexagon 15 mm

4-jaw hydraulic coupler, M10x1  32 438 07

4-jaw hydraulic coupler, R1/8"  32 438 21

4-jaw hydraulic coupler, M10x1  32 438 14

4-jaw hydraulic coupler, R1/8"  32 438 38



4-jaw hydraulic coupler, M10x1  32 438 45

4-jaw hydraulic coupler, R1/8"  32 438 52

4-Jaw Hydraulic Coupler

with backlash valve

High quality hydraulic coupler, DIN 1283, for use with grease fittings DIN 71412. Machined and hardened jaws for optimum leak proof operation, hexagon 15mm. **Integral backlash valve** permits high pressure performance, even with soft greases and oils of lower viscosity.

hydraulic coupler with backlash valve, M10x1 32 440 02

hydraulic coupler with backlash valve, R1/8" 32 440 40

