


PIPE SCREW JOINTS BS WELDING ELBOWS

BS WELDING ELBOWS



description	pipe OD	PN series	S ₁	S ₂	L ₂	l ₂	l ₃	d ₈	kg % pc
DS-BS 6-L	6	L 500	14	12	27	12.0	19	10	3.0
DS-BS 8-L	8	L 500	17	12	29	14.0	23	12	3.6
DS-BS 10-L	10	L 500	19	14	30	15.0	24	14	5.2
DS-BS 12-L	12	L 500	22	17	32	17.0	25	16	7.3
DS-BS 15-L	15	L 400	27	19	36	21.0	30	19	12.0
DS-BS 18-L	18	L 400	32	24	40	23.5	33	22	16.6
DS-BS 22-L	22	L 250	36	27	44	27.5	37	27	24.6
DS-BS 28-L	28	L 250	41	36	47	30.5	42	32	34.7
DS-BS 35-L	35	L 250	50	41	56	34.5	49	40	61.2
DS-BS 42-L	42	L 250	60	50	63	40.0	57	46	84.6
DS-BS 6-S	6	S 800	17	12	31	16.0	23	11	5.2
DS-BS 8-S	8	S 800	19	14	32	17.0	24	13	6.4
DS-BS 10-S	10	S 800	22	17	34	17.5	25	15	9.7
DS-BS 12-S	12	S 630	24	17	38	21.5	29	17	10.8
DS-BS 14-S	14	S 630	27	19	40	22.0	30	19	15.3
DS-BS 16-S	16	S 630	30	24	43	24.5	33	21	18.9
DS-BS 20-S	20	S 400	36	27	48	26.5	37	26	30.3
DS-BS 25-S	25	S 400	46	36	54	30.0	42	31	58.0
DS-BS 30-S	30	S 400	50	41	62	35.5	49	36	74.4
DS-BS 38-S	38	S 400	60	50	72	41.0	57	44	98.9

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.