

Aluminium-Dichtringe

aluminium sealing rings



Flachdichtring Form A nach DIN 7603

Werkstoff: AL 99,5 halbhart = F 20, dies entspricht der von der DIN geforderten Härte von 32 – 45 HB

Betriebstemperatur: nach DIN max. +200° C

flat sealing rings form A according to DIN 7603

material: AL 99,5 semi-rigid = F 20, this corresponds to the hardness of 32 – 45 HB, demanded by the DIN

working temperature: according to DIN max. +200° C

Abmessungen dimensions	Art.-Nr.
5X 9X1	100 402
6X10X1	100 404
6X12X1	100 405
8X12X1	100 407
8X14X1	100 409
8X14X1,5	100 410
10X14X1	100 413
10X16X1	100 415
10X16X1,5	100 416
12X16X1,5	100 418
12X18X1,5	100 419
12X20X1,5	100 420
14X18X1,5	100 422
14X20X1,5	100 424
15X24X1,5	100 427
16X20X1,5	100 428
16X22X1,5	100 429
18X22X1,5	100 430
18X24X1,5	100 431

Abmessungen dimensions	Art.-Nr.
20X26X1,5	100 433
22X27X1,5	100 434
22X29X1,5	100 435
24X30X2	100 436
26X32X2	100 439
28X34X2	100 440
30X36X2	100 442
32X38X2	100 444
35X41X2	100 445
36X42X2	100 446
38X44X2	100 447
40X47X2	100 449
42X49X2	100 448
45X52X2	100 450
52X60X2,5	100 451
56X64X2,5	100 452
60X68X2,5	100 453
64X72X2,5	100 454

Auch im Sortiment lieferbar.
Also available in the assortment.

Fiber-Dichtringe

fiber sealing rings



Flachdichtringe Form A nach DIN 7603

Werkstoff: VF Vulcan-Fiber

Betriebstemperatur: nach DIN max. +100° C

flat sealing rings form A according to DIN 7603

material: VF Vulcan-Fiber

working temperature: according to DIN max. +100° C

Abmessungen dimensions	Art.-Nr.
4X8X1	101 001
4,6X10X1	101 071
5X9X1	101 002
5,2X9,8X2	101 072
6X10X1	101 003
6X12X1	101 004
8X12X1	101 007
8X14X1	101 008
10X14X1,5	101 011
10X16X1,5	101 012
12X16X1,5	101 017
12X19X1,5	101 019
12X20X1,5	101 020
14X18X1,5	101 025
14X20X1,5	101 027
15X24X1,5	101 032

Abmessungen dimensions	Art.-Nr.
16X20X1,5	101 034
16X22X1,5	101 035
18X24X1,5	101 038
20X27X3	101 070
22X27X1,5	101 044
22X29X1,5	101 045
26X32X1,5	101 048
28X34X2	101 051
30X36X2	101 052
32X38X2	101 054
35X41X2	101 056
36X42X2	101 057
38X44X2	101 058
40X47X2	101 060
48X55X7	101 062

Auch im Sortiment lieferbar.
Also available in the assortment.