


Gauge Adaptor SMA-20



Direct Gauge Adaptor SMD-20

Gauge Adaptor SMA-20

Direct Gauge Adaptor SMD-20



Thread	Dimensions (mm/in)		Weight (^{kg} /lbs) ca. per 100	Ordering Codes (Standard Option)
T	h	Hex A		
G1/4	54 2.13	19 .75	7,20 15.84	SMA-20-G1/4-B-OR-W3
G1/2	64 2.52	27 1.06	12,40 27.28	SMA-20-G1/2-B-OR-W3
1/4 NPT	54 2.13	19 .75	7,20 15.84	SMA-20-1/4NPT-W3
1/2 NPT	64 2.52	27 1.06	13,50 29.70	SMA-20-1/2NPT-W3
7/16-20 UNF	54 2.16	19 .75	7,60 16.76	SMA-20-7/16UNF-W3
9/16-18 UNF	57 2.24	19 .75	7,50 16.53	SMA-20-9/16UNF-W3
G1/4	41 1.61	19 .75	5,70 12.54	SMD-20-G1/4-B-OR-W3
G1/2	51 2.01	27 1.06	10,10 22.22	SMD-20-G1/2-B-OR-W3
1/4 NPT	41 1.61	19 .75	5,80 12.76	SMD-20-1/4NPT-W3
1/2 NPT	51 2.01	27 1.06	10,80 23.76	SMD-20-1/2NPT-W3
7/16-20 UNF	41 1.61	19 .75	6,00 13.20	SMD-20-7/16UNF-W3
9/16-18 UNF	43 1.69	19 .75	5,25 11.55	SMD-20-9/16UNF-W3

Ordering Codes

SMA-20*-G1/4*-B*-OR*-W3

* Type	Gauge Adaptor	SMA
* Series	STAUFF Test 20 (Connection Thread M16x2)	-20
* Thread	acc. to dimension table	-G1/4
* Seal Material	NBR (Buna-N®) FKM (Viton®) EPDM Seal Type without O-ring	-B -V -E none
* Seal Type	with O-ring	-OR
* Material Code	Steel, zinc/nickel-plated Stainless Steel V2A - 1.4305 (AISI 303) Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W3 -W4 -W5

Standard option - SMA-20: With Hexagon Lock Nut.

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.
Snubber on request.