

O-Ringe - zöllig

O-rings - inch

75 Shore

Werkstoff: FKM

Farbe: grün

Temperatur: -20° C bis +200° C

75 Shore

material: FKM

colour: green

working temperature: -20° C to +200° C



Innen-Ø mm Inner-Ø mm	Schnur-Ø mm Cord-Ø mm	Art.-Nr.
2,90	1,78	416 391 006
3,68	1,78	416 391 007
4,47	1,78	416 391 008
6,07	1,78	416 391 009
7,65	1,78	416 391 011
9,25	1,78	416 391 012
10,82	1,78	416 391 013
12,42	1,78	416 391 014
14,00	1,78	416 391 015
15,60	1,78	416 391 016
17,17	1,78	416 391 017
18,77	1,78	416 391 018
21,95	1,78	416 391 020
23,52	1,78	416 391 021
25,12	1,78	416 391 022
29,87	1,78	416 391 025
37,82	1,78	416 391 029
41,00	1,78	416 391 030
44,17	1,78	416 391 031

Innen-Ø mm Inner-Ø mm	Schnur-Ø mm Cord-Ø mm	Art.-Nr.
6,02	2,62	416 393 108
7,59	2,62	416 393 109
9,19	2,62	416 393 110
10,77	2,62	416 393 111
13,94	2,62	416 393 113
15,54	2,62	416 393 114
17,12	2,62	416 393 115
18,72	2,62	416 393 116
20,29	2,62	416 393 117
21,89	2,62	416 393 118
23,47	2,62	416 393 119
25,07	2,62	416 393 120
26,64	2,62	416 393 121
28,24	2,62	416 393 122
29,82	2,62	416 393 123
31,42	2,62	416 393 124
32,99	2,62	416 393 125
34,59	2,62	416 393 126
36,17	2,62	416 393 127
37,77	2,62	416 393 128
39,34	2,62	416 393 129

42,52	2,62	416 393 131
44,12	2,62	416 393 132
45,69	2,62	416 393 133
47,29	2,62	416 393 134
48,90	2,62	416 393 135
50,47	2,62	416 393 136
52,07	2,62	416 393 137
53,64	2,62	416 393 138
55,25	2,62	416 393 139
56,82	2,62	416 393 140
58,42	2,62	416 393 141
59,99	2,62	416 393 142
64,77	2,62	416 393 145
66,34	2,62	416 393 146
67,95	2,62	416 393 147
69,52	2,62	416 393 148
72,69	2,62	416 393 150
75,87	2,62	416 393 151
82,22	2,62	416 393 152
101,27	2,62	416 393 155
120,32	2,62	416 393 158
158,42	2,62	416 393 164
171,12	2,62	416 393 166

Innen-Ø mm Inner-Ø mm	Schnur-Ø mm Cord-Ø mm	Art.-Nr.
13,87	3,53	416 395 207
15,47	3,53	416 395 208
17,04	3,53	416 395 209
18,64	3,53	416 395 210
20,22	3,53	416 395 211
21,82	3,53	416 395 212
23,39	3,53	416 395 213
26,57	3,53	416 395 215
28,17	3,53	416 395 216
29,74	3,53	416 395 217
31,34	3,53	416 395 218
32,92	3,53	416 395 219
34,52	3,53	416 395 220
36,09	3,53	416 395 221
37,69	3,53	416 395 222
40,87	3,53	416 395 223
44,04	3,53	416 395 224
47,22	3,53	416 395 225
53,57	3,53	416 395 227
56,74	3,53	416 395 228
63,09	3,53	416 395 230
66,27	3,53	416 395 231

69,44	3,53	416 395 232
72,62	3,53	416 395 233
75,79	3,53	416 395 234
78,97	3,53	416 395 235
82,14	3,53	416 395 236
85,32	3,53	416 395 237
88,49	3,53	416 395 238
91,67	3,53	416 395 239
94,84	3,53	416 395 240
98,02	3,53	416 395 241
101,19	3,53	416 395 242
104,37	3,53	416 395 243
107,54	3,53	416 395 244
110,72	3,53	416 395 245
120,24	3,53	416 395 248
123,42	3,53	416 395 249
126,59	3,53	416 395 250
129,77	3,53	416 395 251
132,94	3,53	416 395 252
136,12	3,53	416 395 253
142,47	3,53	416 395 255
148,82	3,53	416 395 257
151,99	3,53	416 395 258
171,04	3,53	416 395 261
183,74	3,53	416 395 263
190,09	3,53	416 395 264
196,44	3,53	416 395 265
202,79	3,53	416 395 266
209,14	3,53	416 395 267
215,49	3,53	416 395 268
253,59	3,53	416 395 274
291,69	3,53	416 395 277

Innen-Ø mm Inner-Ø mm	Schnur-Ø mm Cord-Ø mm	Art.-Nr.
15,24	5,33	416 397 312
23,16	5,33	416 397 317
24,77	5,33	416 397 318
27,94	5,33	416 397 320
34,29	5,33	416 397 324
37,47	5,33	416 397 325
40,64	5,33	416 397 326
43,82	5,33	416 397 327
46,99	5,33	416 397 328
50,17	5,33	416 397 329
53,34	5,33	416 397 330
56,52	5,33	416 397 331