


EOLO TERMORESISTENTE



IT Tubo flessibile di colore grigio realizzato con tessuto di poliestere spalmato in PVC autoestinguente. Spirale di rinforzo in acciaio incorporata tra i due strati. Il materiale è autoestinguente secondo UL 94 V(TM)-0 e secondo NFP 92 503 (grado M2). Comprimibilità assiale 8:1.

• Impianti di condizionamento civile e navale, ventilazione, aspirazione di fumi, vapori, polveri e gas.

EN Grey flexible hose made of flame-resistant PVC coated polyester fabric, reinforced with a steel spiral embedded between the two layers. The material is flame retardant, according to UL 94 V(TM)-0 and to NFP 92 503 (M2 grade). Axial compressibility 8:1.

• Civil and naval air conditioning systems, ventilation, fumes, vapours, dust and gas extraction.

COD. TR 01

Ø mm 40-505




spirale in acciaio
steel spiral

Tessuto di poliestere spalmato di PVC autoestinguente
Flame resistant PVC coated polyester fabric

SCHEDA TECNICA - TECHNICAL DATA



disponibile a magazzino
available on stock




F2 W2 p.122
Fascetta doppioponte W2 / Double bridge W2

ARTICOLI DELLA STESSA SERIE ITEMS IN THE SAME SERIES



EOLO HT 180°C (cod. H1) p.47



SILDUCT 2S (cod. P43) p.52

CODICE CODE	Ø INT. Ø INT.	PESO WEIGHT	DEPRESSIONE VACUUM	R. CURVATURA BENDING	LG. ROTOLO COIL LGTH.	VOL. VOL.
	mm	g/m	m H ₂ O	mm	m	m ³
TR01040000000	40	115	1,5	20	10	0,002
TR01045000000*	45	125	1,2	23	10	0,002
TR01051000000	51	135	1,2	26	10	0,003
TR01055000000*	55	145	1,2	28	10	0,003
TR01060000000	60	160	1,2	30	10	0,004
TR01063000000	63	165	1,2	32	10	0,004
TR01065000000*	65	170	1,2	33	10	0,005
TR01070000000	70	165	1,2	35	10	0,005
TR01073000000*	73	175	1,2	37	10	0,006
TR01076000000	76	180	1,0	38	10	0,006
TR01080000000	80	190	1,2	40	10	0,007
TR01082000000*	82	195	1,2	41	10	0,007
TR01090000000	90	210	1,0	45	10	0,009
TR01102000000	102	275	1,0	51	10	0,011
TR01107000000*	107	290	0,8	54	10	0,012
TR01110000000	110	300	0,8	55	10	0,013
TR01115000000	115	310	0,8	58	10	0,014
TR01120000000	120	325	0,8	60	10	0,015
TR01125000000*	125	340	0,8	63	10	0,016
TR01127000000	127	345	0,6	64	10	0,017
TR01130000000	130	350	0,6	65	10	0,018
TR01140000000	140	380	0,6	70	10	0,021
TR01152000000	152	410	0,6	76	10	0,024
TR01160000000	160	420	0,5	80	10	0,027
TR01163000000*	163	430	0,5	82	10	0,028
TR01170000000*	170	445	0,5	85	10	0,030
TR01180000000	180	475	0,5	90	10	0,034
TR01200000000*	200	525	0,5	100	10	0,041
TR01203000000	203	535	0,5	102	10	0,043
TR01228000000	228	600	0,4	114	10	0,054
TR01230000000*	230	600	0,4	115	10	0,055
TR01254000000	254	840	0,4	127	10	0,067
TR01279000000*	279	920	0,3	140	10	0,080
TR01305000000	305	1005	0,3	153	10	0,124
TR01310000000*	310	1020	0,2	155	10	0,099
TR01315000000*	315	1040	0,2	158	10	0,102
TR01330000000*	330	1090	0,1	165	10	0,112
TR01356000000	356	1175	0,1	178	10	0,130
TR01406000000	406	1335	0,05	203	10	0,168
TR01455000000*	455	1875	0,05	228	10	0,211
TR01500000000*	500	2055	0,02	250	10	0,255
TR01505000000*	505	2080	0,02	253	10	0,260

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.