


PIPE SCREW JOINTS

K STRAIGHT BULKHEAD CONNECTIONS

K STRAIGHT BULKHEAD CONNECTIONS



description	pipe OD	PN series	S	S ₁	S ₃	L ₁	l ₁	Dmax	L ₃	l ₃	M	kg % pc
DS-K 6-L	6	L 500 (2200)	17	14	17	22	7.0	16	42	27.0	M 12x1.5	6.7
DS-K 8-L	8	L 500 (2200)	19	17	19	23	8.0	16	42	27.0	M 14x1.5	8.4
DS-K 10-L	10	L 500 (2200)	22	19	22	25	10.0	16	43	28.0	M 16x1.5	11.0
DS-K 12-L	12	L 400 (1700)	24	22	24	25	10.0	16	44	29.0	M 18x1.5	13.3
DS-K 15-L	15	L 400 (1700)	27	27	30	27	12.0	16	46	31.0	M 22x1.5	22.8
DS-K 18-L	18	L 400 (1700)	32	32	36	30	13.5	16	49	32.5	M 26x1.5	33.2
DS-K 22-L	22	L 250 (1100)	36	36	41	33	16.5	16	51	34.5	M 30x2	41.5
DS-K 28-L	28	L 250 (1100)	41	41	46	35	18.5	16	52	35.5	M 36x2	52.5
DS-K 35-L	35	L 250 (1100)	50	50	55	40	18.5	16	58	36.5	M 45x2	80.0
DS-K 42-L	42	L 250 (1100)	60	60	65	42	19.0	16	59	36.0	M 52x2	119.3
DS-K 6-S	6	S 800 (3400)	19	17	19	27	12.0	16	44	29.0	M 14x1.5	9.6
DS-K 8-S	8	S 800 (3400)	22	19	22	28	13.0	16	44	29.0	M 16x1.5	12.4
DS-K 10-S	10	S 800 (3400)	24	22	24	31	14.5	16	46	29.5	M 18x1.5	18.1
DS-K 12-S	12	S 630 (2700)	27	24	27	31	14.5	16	47	30.5	M 20x1.5	21.0
DS-K 14-S	14	S 630 (2700)	30	27	30	35	17.0	16	50	32.0	M 22x1.5	29.0
DS-K 16-S	16	S 630 (2700)	32	30	32	35	16.5	16	50	31.5	M 24x1.5	31.0
DS-K 20-S	20	S 400 (1700)	41	36	41	39	17.5	16	55	33.5	M 30x2	54.5
DS-K 25-S	25	S 400 (1700)	46	46	46	44	20.0	16	59	35.0	M 36x2	89.0
DS-K 30-S	30	S 400 (1700)	50	50	50	48	21.5	16	64	37.5	M 42x2	107.7
DS-K 38-S	38	S 400 (1700)	65	60	65	53	22.0	16	68	37.0	M 52x2	173.0

$L_1 + L_3$ = approximate length with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.