



2004 PVC Hose



DESCRIPTION

Grey corrugated suction hose. Ideal for use as vacuum-cleaner hose and extraction hose for welding equipment, etc.

Vacuum: 60%. The hose is not antistatic.

Note! The hose is supplied in 20, 63 and 76 metre length.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2004
Application	Industrial Vacuum, EVA
Standard length	20, 63 and 76 metres
Working temp.	-40°C to 60°C
Inside compound	EVA
Inside colour	Grey
Outside compound	-
Outside colour	Grey
Reinforcement	-
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
32,0	40,0	â€“	â€“	90	280	2004032000
38,0	47,3	â€“	â€“	100	295	2004038000
45,0	54,5	â€“	â€“	125	380	2004045000
50,0	60,3	â€“	â€“	150	430	2004050000
63,0	75,0	â€“	â€“	250	575	2004063000
76,0	88,0	â€“	â€“	300	641	2004076000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Denmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.
End of life evaluation for production of Rubber hoses with Textile reinforcement