





CONFIGURATION

L	Control	Standard Screw Adjustment
N	Adjustment Range	75 - 800 psi (5 - 55 bar), 400 psi (28 bar) Standard Setting
N	Seal Material	Buna-N
(none) Material/Coating		

Pilot-operated, balanced-piston relief cartridges are normally closed pressure regulating valves. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to regulate the pressure. These valves are accurate, have low pressure rise vs. flow, they are smooth and quiet, and are moderately fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-162A
Series	0
Capacity	12 gpm
Maximum Operating Pressure	5000 psi
Factory Pressure Settings Established at	4 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in ³ /min.@1000 psi
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	3/4 in.
Valve Installation Torque	20 - 25 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	1/2 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	EPDM: 990162014
Seal kit - Cartridge	Polyurethane: 990162002
Seal kit - Cartridge	Viton: 990162006
Model Weight	0.21 lb.

CONFIGURATION OPTIONS

Model Code Example: RPCCLNN

CONTROL	(L)	ADJUSTMENT RANGE	(N)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		N 75 - 800 psi (5 - 55 bar), 400 psi (28 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set				E EPDM		/AP Stainless Steel, Passivated
K Handknob		A 75 - 3000 psi (5 - 210 bar), 1000 psi (70 bar) Standard Setting		V Viton		/LH Mild Steel, Zinc-Nickel
		W 75 - 4500 psi (5 - 315 bar), 1000 psi (70 bar) Standard Setting				
		B 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting				
		C 75 - 6000 psi (5 - 420 bar), 1000 psi (70 bar) Standard Setting				
		Q 75 - 400 psi (5 - 28 bar), 200 psi (14 bar) Standard Setting				

TECHNICAL FEATURES

- All 2-port relief cartridges (except pilot reliefs) are physically and functionally interchangeable (same flow path, same cavity for a given frame size).
- Will accept maximum pressure at port 2; suitable for use in cross port relief circuits. If used in cross port relief circuits, consider spool leakage.
- Minimum setting is 75 psi (5 bar) for all spring ranges.
- Not suitable for use in load holding applications due to spool leakage.
- Back pressure on the tank port (port 2) is directly additive to the valve setting at a 1:1 ratio.
- The main stage orifice is protected against contamination.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

