




PUR Hose Kits – with Adapters and Accessories

- **Hose kits in different configurations**
- **Light and flexible hose**
- **Pre-assembled and ready to use**

CEJN Hose Kits are available as spiral hose pre-assembled with: swivel adapters, fixed adapters or different types of blowguns. Each kit is ready for immediate use without the need for tools. The content of the kits are reusable, airtight and will not need follow-up tightening.



	Service length	Part No.	ID x OD	Connection 1	Connection 2	Description
SWIVEL & THREADED 	6.6 °F (2.0 m)	19 958 9978	(5 x 8 mm)	R 1/4" swiveling	R 1/4" swiveling	-
		19 958 9947	(6.5 x 10 mm)	R 1/4" swiveling	R 1/4" swiveling	-
		19 958 9997	(8 x 12 mm)	R 3/8" swiveling	R 3/8" swiveling	-
	13.1 °F (4.0 m)	19 958 9965	(5 x 8 mm)	R 1/4" swiveling	R 1/4" swiveling	-
		19 958 9949	(6.5 x 10 mm)	R 1/4" swiveling	R 1/4" swiveling	-
		19 958 9967	(8 x 12 mm)	R 3/8" swiveling	R 3/8" swiveling	-
	19.7 °F (6.0 m)	19 958 9810	(11 x 16 mm)	R 1/2" swiveling	R 1/2" swiveling	-
		19 958 9954	(6.5 x 10 mm)	R 1/4" swiveling	R 1/4" swiveling	-
	26.2 °F (8.0 m)	19 958 9998	(8 x 12 mm)	R 3/8" swiveling	R 3/8" swiveling	-
		19 958 9957	(6.5 x 10 mm)	R 1/4" swiveling	R 1/4" swiveling	-
		19 958 9809	(8 x 12 mm)	R 3/8" swiveling	R 3/8" swiveling	-
		19 958 9346	(11 x 16 mm)	R 1/2" swiveling	R 1/2" swiveling	-
19 958 9987		(6.5 x 10 mm)	R 1/4"	R 1/4"	-	
FIXED & THREADED 	6.6 °F (2.0 m)	19 958 9325	(5 x 8 mm)	R 1/4"	R 1/4"	-
		19 958 9988	(6.5 x 10 mm)	R 1/4"	R 1/4"	-
	13.1 °F (4.0 m)	19 958 9805	(8 x 12 mm)	R 3/8"	R 3/8"	-
		19 958 9885	(11 x 16 mm)	R 1/2"	R 1/2"	-
		19 958 9955	(6.5 x 10 mm)	R 1/4"	R 1/4"	-
	19.7 °F (6.0 m)	19 958 9804	(8 x 12 mm)	R 3/8"	R 3/8"	-
		19 958 9801	(8 x 12 mm)	R 3/8"	R 3/8"	-
	26.2 °F (8.0 m)	19 958 9862	(11 x 16 mm)	R 1/2"	R 1/2"	-
		19 958 9326	(5 x 8 mm)	320 nipple	320 coupling	208 Star-Tip. Removable tube + Assembled nipple
	HOSE KITS WITH BLOW-GUN 	6.6 °F (2.0 m)	19 958 9327	(6.5 x 10 mm)	320 nipple	320 coupling
19 958 9328			(6.5 x 10 mm)	320 nipple	320 coupling	208 Star-Tip. Removable tube + Assembled nipple
13.1 °F (4.0 m)		19 958 9746	(6.5 x 10 mm)	320 nipple	320 coupling	208 Star-Tip. 10-320-1152+Nipple assembled on blowgun
		19 958 9360	(6.5 x 10 mm)	320 nipple	320 coupling	210 MultiFLOW adjustable nozzle+ assembled nipple
		19 958 9332	(8 x 12 mm)	320 nipple	320 coupling	208 Std. Fixed tube + Assembled nipple
		19 958 9333	(8 x 12 mm)	310 nipple	310 coupling	208 Std. Fixed tube + Assembled nipple
19.7 °F (6.0 m)		19 958 9361	(8 x 12 mm)	320 nipple	320 coupling	210 MultiFLOW adjustable nozzle+ assembled nipple
		19 958 9329	(6.5 x 10 mm)	300 nipple	300 coupling	208 Star-Tip. Removable tube + Assembled nipple
19 958 9334	(8 x 12 mm)	320 nipple	320 coupling	208 Std. Fixed tube + Assembled nipple		

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, www.cejn.com, for general maintenance tips.