


DIN 24° FDHORX

Female DIN 'O' ring swivel. 24° cone.

Heavy series.




D				A	B	H	REF.
-size	DN	"		mm	mm	mm	GS
-6	10	3/8	M20 x 1.5	73.0	37.2	24.0	6GS12FDHORX
-6	10	3/8	M22 x 1.5	75.5	39.7	27.0	6GS14FDHORX
-8	12	1/2	M20 x 1.5	72.5	35.0	24.0	8GS12FDHORX
-8	12	1/2	M22 x 1.5	76.5	38.9	27.0	8GS14FDHORX
-8	12	1/2	M24 x 1.5	79.0	41.5	30.0	8GS16FDHORX
-8	12	1/2	M30 x 2.0	82.0	44.5	36.0	8GS20FDHORX
-10	16	5/8	M24 x 1.5	96.0	45.7	30.0	10GS16FDHORX
-10	16	5/8	M30 x 2.0	100.0	49.7	36.0	10GS20FDHORX
-10	16	5/8	M36 x 2.0	104.0	53.7	46.0	10GS25FDHORX
-12	20	3/4	M30 x 2.0	103.0	52.0	36.0	12GS20FDHORX
-12	20	3/4	M36 x 2.0	107.4	56.4	46.0	12GS25FDHORX
-12	20	3/4	M42 x 2.0	97.0	46.0	50.0	12GS30FDHORX
-16	25	1	M36 x 2.0	116.0	59.6	46.0	16GS25FDHORX
-16	25	1	M42 x 2.0	118.0	61.6	50.0	16GS30FDHORX
-16	25	1	M52 x 2.0	111.8	55.1	38.0	16GS38FDHORX
-20	32	1.1/4	M52 x 2.0	145.0	73.9	60.0	20GS38FDHORX
-24	40	1.1/2	M52 x 2.0	150.0	76.4	60.0	24GSP38FDHORX

-6 to -20 size are 42.0 MPa (6000 psi).

DIN 24° FDHORX-RB

Female DIN 'O' ring swivel. 24° cone.

Heavy series. Rockbreaker version.



D				A	B	H	REF.
-size	DN	"		mm	mm	mm	GS
-10	16	5/8	M30 x 2.0	100.0	49.7	36.0	10GS20FDHORX-RB
-12	20	3/4	M36 x 2.0	107.4	56.4	46.0	12GS25FDHORX-RB
-16	25	1	M42 x 2.0	118.0	61.6	50.0	16GS30FDHORX-RB
-20	32	1.1/4	M52 x 2.0	145.0	73.9	60.0	20GS38FDHORX-RB

Unless otherwise stated the coupling meets the pressure rating requirements of the respective international standard.