



Feuerschutzschlauch mit Klettverschluss - EN45545 / DIN5510-2

Fire protection hose with hook & loop closure - EN45545 / DIN5510-2
Tuyau de protection contre l'incendie avec velcro - EN45545 / DIN5510-2
Manguera de protección contra incendios con velcro - EN45545 / DIN5510-2
Wąż przeciwpożarowy z zapięciem na rzep - EN45545 / DIN5510-2
Protezione antifiamma per tubi con velcro - EN45545 / DIN5510-2

Beschreibung:

Silikonbeschichtetes
Fiberglas mit Klettver-
schluss

Betriebstemperatur:

max 260°C kurzfristig
1100°C

Norm:

EN45545 und DIN5510-2
UL 1441

Rollenware:

<= DN75 20m
> DN75 10m
(kein Anschnitt)

Desription:

Silicone coated fiberglas
with loop closure

Temperature:

max 260°C short time
1100°C

Norm:

EN45545 and DIN5510-2
UL 1441

Coil:

<= DN75 20m
> DN75 10m
(no short lengths
available)

Part-No.	 mm	 mm	 bar	 mm	 %	 g/m	Price/m
SSCF-15-W	15	19,2					
SSCF-20-W	20	25					
SSCF-25-W	25	30,2					
SSCF-30-W	30	35,8					
SSCF-35-W	35	41,2					
SSCF-40-W	40	46,8					
SSCF-45-W	45	52					
SSCF-50-W	50	57,4					
SSCF-55-W	55	62,8					
SSCF-60-W	60	68					
SSCF-65-W	65	73,2					
SSCF-70-W	70	78,6					
SSCF-75-W	75	83,8					
SSCF-80-W	80	89					
SSCF-90-W	90	100					
SSCF-95-W	95	105					
SSCF-100-W	100	112					



Silikon Vulkanisierband

Silicone vulcanising tape
Bande de vulcanisation en silicone
Cinta vulcanizadora de silicona
Silikonowa taśma wulkanizacyjna
Nastro vulcanizzante in silicone

NEW

Part-No.	Colour	Length	Thickness	Width	Price
VB01-10M	Red	10m	0,5mm	25mm	
VB02-10M	Black	10m	0,5mm	25mm	