


Welding Adaptor SAS



Ordering Codes


SAS-M10x1*-W2

* Type	Welding Adaptor	SAS
* Port Connection	acc. to dimension table	-M10x1
* Material Code	Steel, untreated	-W1
	Steel, phosphated	-W2
	Stainless Steel V2A - 1.4305 (AISI 303)	-W4
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W5

Thread	Port Connection	Dimensions (mm/in)		Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
T		h	Ød		
M10 x 1	Type A (p. 74)	25 .98	20 .79	4,60 10.14	SAS-M10x1-W2
G1/8	Type B/C (p. 75)	25 .98	20 .79	4,70 10.36	SAS-G1/8-W2
G1/4		30 1.18	22 .87	6,40 14.11	SAS-G1/4-W2
G3/8		30 1.18	25 .98	6,90 21.16	SAS-G3/8-W2
1/4 NPT	Type D (p. 76)	25 .98	20 .79	3,80 8.38	SAS-1/4NPT-W2
1/2-20 UNF	Type E (p. 77)	25 .98	20 .79	14,00 30.86	SAS-1/2UNF-W2

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Adjustable Gauge Fitting EMV



Ordering Codes

EMV-G1/4/G1/2*-B*-OR*-B*-C*-W3

* Type	Adjustable Gauge Fitting	EMV
* Port Connection	acc. to dimension table	-G1/4/G1/2
* Seal Material	NBR (Buna-N®)	-B
	FKM (Viton®)	-V
	EPDM	-E
* Seal Type (Female)	with O-ring	-OR
* Seal Material	NBR (Buna-N®)	-B
* Seal Type	Elastomeric Sealing Type C	-C
* Material Code	Steel, zinc/nickel-plated	-W3
	Stainless Steel V2A - 1.4305 (AISI 303)	-W4
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W5

Dimensions (mm/in)				Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
T1	T2	h	Hex		
G1/4	G1/4	42 1.65	19 .75	6,20 13.64	EMV-G1/4-B-OR-B-C-W3
G1/4	G1/2	47 1.85	19 .75	11,10 24.42	EMV-G1/4/G1/2-B-OR-B-C-W3
G1/2	G1/4	51 2.01	27 1.06	13,00 28.60	EMV-G1/2/G1/4-B-OR-B-C-W3
G1/2	G1/2	55,5 2.19	27 1.06	18,00 39.60	EMV-G1/2-B-OR-B-C-W3

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.