



INTERPUMP

FLUID SOLUTIONS 

Powered by I.M.M. Hydraulics



LONG LIFE ANTIABRASION COVER
THE BEST CHOICE FOR SEWER APPLICATION

 **INTERPUMP**  *Long Life* EXCEEDS EN 857 - 2SC

Long Life



INTERPUMP

FLUID SOLUTIONS

Powered by I.M.M. Hydraulics

INTERPUMP LONGLIFE for SEWERJET APPLICATION

Our standard high-end LongLife hydraulic hose is today also available for Sewerjet application.

IMPROVEMENTS:

- The anti-abrasive cover will exceed 25 time std ISO 6945
- The safety factor will be 3:1 for size up to the 1"
- High ozone and weather conditions resistance



LongLife

- **Internal hose:** Synthetic rubber, extruded whole without joints, of uniform thickness.
- **Reinforcement:** 1 or 2 steel wires braids
- **Recommended fluid:** Mineral and biological oils, glycol-water based, water, lubricants.

Part number													
	ID		Size	OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm		mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE201K-06	3/8"	9.5	6	15.7	280	4060	1000	14500	60	2.362	0.248	0.167	001C-06
THE202K-08	1/2"	12.7	8	20.4	310	4495	1240	17980	80	3.150	0.521	0.350	001C-08
THE202K-12	3/4"	19.0	12	27.6	300	4350	960	13920	100	3.937	0.764	0.513	001C-12
THE202K-16	1"	25.4	16	35.8	280	4060	740	10730	130	5.188	1.171	0.787	001C-16
THE202K-20**	1.1/4"	31.8	20	43.1	250	3625	640	9280	200	7.874	1.530	1.028	001C-20

(*) Min BP e Min BR relating to SEWER jetting application

(**) Available on standard wrapped cover only. Max length 60mt.



INTERPUMP



LongLife

EXCEEDS EN 857 - 2SC DN 19 I.D. 3/4" - W.P. 24,0 MPa/3480 psi - ISO 7751 S.F. 3:1 W.P. 30,0 MPa

www.interpumpfluidsolutions.com