



Test Coupling with 24° Taper / O-ring (DKO) SMK-10 Type K



Version A



Version B

Ordering Codes

SMK-10*-18L*-B*-K*-GS*-W3

* Type	Test Coupling with Ball Check	SMK
* Series	STAUFF Test 10 Plug In System	-10
* Outside Tube Diameter	acc. to dimension table	-18
* Series	Light Series Heavy Series	L S
* Seal Material	NBR (Buna-N®) FKM (Viton®) EPDM	-B -V -E
* Connection	24° Taper / O-ring (DKO)	-K
* Design	One-piece design (Version A) Screwed design (Version B)	- -GS
* Material Code	Steel, zinc/nickel-plated Stainless Steel V2A - 1.4305 (AISI 303) Stainless Steel V4A - 1.4571 (AISI 316 Ti)	-W3 -W4 -W5

Series	PN (^{bar} /psi)	Pipe	Dimensions (mm/in)		Thread	Version	Weight (^{kg} /lbs) ca.	Ordering Codes (Standard Option)
		Ø d	I3	Hex A			per 100	
L	315 4568	6	15,5 .61	14 .55	M12 x 1,5	A	4,60 10.12	SMK-10-06L-B-K-GS-W3
		8	15,5 .61	17 .67	M14 x 1,5	A	5,30 11.66	SMK-10-08L-B-K-GS-W3
		10	16,5 .65	19 .75	M16 x 1,5	A	6,50 14.30	SMK-10-10L-B-K-GS-W3
		12	17,5 .69	22 .87	M18 x 1,5	A	8,00 17.60	SMK-10-12L-B-K-GS-W3
		15	21 .83	27 1.06	M22 x 1,5	B	8,10 17.82	SMK-10-15L-B-K-GS-W3
		18	19,5 .77	32 1.26	M26 x 1,5	B	10,90 23.98	SMK-10-18L-B-K-GS-W3
	160 2320	22	20,5 .81	36 1.42	M30 x 2	B	15,30 33.66	SMK-10-22L-B-K-GS-W3
		28	25 .98	41 1.61	M36 x 2	B	21,10 270.51	SMK-10-28L-B-K-GS-W3
		35	30 1.18	50 1.97	M45 x 2	B	35,75 78.82	SMK-10-35L-B-K-GS-W3
		42	31 1.22	60 2.36	M52 x 2	B	53,10 117.07	SMK-10-42L-B-K-GS-W3
S	400 5801	6	14,5 .57	17 .67	M14 x 1,5	A	5,10 11.22	SMK-10-06S-B-K-GS-W3
		8	16,5 .65	19 .75	M16 x 1,5	A	6,10 13.42	SMK-10-08S-B-K-GS-W3
		10	16,5 .65	22 .87	M18 x 1,5	A	7,80 17.16	SMK-10-10S-B-K-GS-W3
		12	17,5 .69	24 .94	M20 x 1,5	A	9,80 21.56	SMK-10-12S-B-K-GS-W3
		14	19,5 .77	27 1.06	M22 x 1,5	B	8,60 18.92	SMK-10-14S-B-K-GS-W3
		16	18 .71	30 1.18	M24 x 1,5	B	10,20 22.44	SMK-10-16S-B-K-GS-W3
		20	24 .94	36 1.42	M30 x 2	B	17,00 37.40	SMK-10-20S-B-K-GS-W3
		25	26 1.02	46 1.81	M36 x 2	B	30,70 67.54	SMK-10-25S-B-K-GS-W3
		30	30 1.18	50 1.97	M42 x 2	B	37,80 83.33	SMK-10-30S-B-K-GS-W3
		315 4568	38	34 1.34	60 2.36	M52 x 2	B	59,50 131.18

With 24° Taper / O-ring (DKO) Connection acc. to ISO 8434-1 / DIN 2353

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

